



## OMNIKEY® 5513 Reader Board Compact Mifare Easy

<b>Description</b>	<p>The <b>OMNIKEY® 5513 Reader Board Compact</b> is a contact less proximity read/write device that supports various RFID-devices out of the Mifare® family and the ISO 14443 A standard. The module comes with an integrated and optimized antenna for a quick and easy integration into applications. By using the serial interface the device easily can be connected to a controller or any host system. The form factor enables a design in even into very compact systems.</p>	<ul style="list-style-type: none"> <li>• E-Payment</li> <li>• E-Toll Road Pricing</li> <li>• E-Ticketing for Events</li> <li>• E-Ticketing for Public Transport</li> <li>• Access Control</li> <li>• PC Access</li> <li>• Authentication</li> <li>• Printer</li> <li>• Production Equipment</li> </ul>
--------------------	--	--

<b>Product Code:</b>	<b>RDHC-0502N0-01</b>		
<b>RF Transmit Frequency</b>	13.56MHz		
<b>Supported Standards</b>	ISO14443A		
<b>Supported Tag-ICs</b>	Mifare® Standard	SLE66R35	ISO 14443A Tags
	Mifare® 4k	SLE44R35	
	Mifare® Pro X		
	Mifare® Ultralight		
	Mifare® DESFire (Serial No. only)		
<b>Host Communication</b>	Point-to-Point		
<b>Communications Interface</b>	RS232		
<b>Communications Protocol</b>	Specific ASCII and Binary Protocol		
<b>Communications Parameter</b>	9600 Bit/s to 57600 Bit/s, 8, N, 1		
<b>Firmware Boot-Loader</b>	no		
<b>S/W Driver</b>	Virtual COM Port, API - DLL		
<b>Power Supply</b>	5VDC ± 10% regulated		
<b>Power Consumption</b>	150 mA < 10mA at power down mode		

<b>Product Code:</b>	<b>RDHC-0502N0-01</b>
<b>Reading distance</b>	Up to 85mm, depending on tag and antenna
<b>RF Transmission Speed</b>	106 kBit/s
<b>Antenna</b>	Integrated
<b>Input/Output Connector</b>	2 status indicator LED lines, 1 I/O Port
<b>Size</b>	(LxWxH) 70.0x45.0x12.1mm ± 1.0mm / 2.76x1.77x0.48 Inch ± 0.04 Inch
<b>Weight</b>	16g ± 10% / 0.04 lb± 10%
<b>Operating Temperature</b>	-20°C to + 80°C / -4F to +176F
<b>Storage Temperature</b>	-40°C to + 85°C / -40F to +185F
<b>Firmware Version</b>	1.0
<b>Approvals/Compliances</b>	EN 300-330, CE, FCC Part 15, RoHS compliant
<b>MTBF</b>	200.000 h