



**Data Sheet**

**Cards & Inlays**



**sokymot**

**ISO Card  
I-Code SLI-S**

<b>Description</b>	<b>Proximity ISO card, flexible card designed to suit most 13.56 MHz applications</b>		
<b>IC type:</b>	I-Code SLI-S		
<b>Physical:</b>	Thickness:	0.76 mm	± 0.08 mm
	Length:	85.60 mm	± 0.12 mm
	Width:	53.98 mm	± 0.05 mm
	Color:	White / white	
<b>Electrical:</b>	Operating Frequency:	13.56 MHz	
<b>Operating temp:</b>	-35 <sup>o</sup> C to +50 <sup>o</sup> C	(-30 <sup>o</sup> F to +122 <sup>o</sup> F)	ISO/IEC 10373
<b>Resistance:</b>	Dynamic bending and torsion stress tested		ISO/IEC 7816-1 and 10373
<b>Material:</b>	PVC, white / white (glossy)		
<b>Contact module:</b>	Customer may embed a contact module at ISO position		ISO/IEC 7816-1
<b>Magnetic stripe:</b>	HiCo and LoCo magstripe in ISO position upon request		
<b>Printing:</b>	Both sides are fully printable with various technologies		
<b>Options:</b>	For full options list, please visit our website: <a href="http://www.aaitg.com">www.aaitg.com</a>		
<b>Part number:</b>	<b>67040X</b>		