



**Data Sheet**

**Cards & Inlays**



**sokymat**

**EPOXY KEYFOB  
UNIQUE**

Description	Proximity Keyfob designed to suit most 125 kHz proximity systems		
<b>IC type:</b>	UNIQUE (EM4x02)		
<b>Physical:</b>	Thickness:	1.6 mm	± 0.20 mm
	Length:	45 mm	± 0.20 mm
	Width:	30 mm	± 0.20 mm
	Color:	Black	
<b>Electrical:</b>	Operating Frequency:	125 kHz	± 6 kHz
<b>Storage temp:</b>	-40°C to +95°C	(-40°F to +203°F)	ISO/IEC 10373
<b>Operating temp:</b>	-40°C to +85°C	(-40°F to +185°F)	ISO/IEC 10373
<b>Mechanical:</b>	Drop test 10 times 10 cycles (1.8m)		
<b>Resistance:</b>	The Keyfob is designed to resist common stress known from access control and time and attendance systems		
<b>Material:</b>	Epoxy		
<b>Immersion:</b>	Water IP67		ISO/IEC 60529
<b>Printing:</b>	Both sides are printable and laser-engravable with various technologies		
<b>Options:</b>	For full options list, please visit our website: <a href="http://www.aaitg.com">www.aaitg.com</a>		
<b>Part number:</b>	<b>601140</b>		