



Data Sheet

Industry & Logistics



sokymat

**LOGI TAG 160
Unique**

Chip type:	UNIQUE – read only 64bits		* Test conditions and remarks
Physical:	Diameter:	16 mm ± 0.1 mm	
	Thickness:	3 mm ± 0.1 mm	
	Weight:	1.1g	
	Material:	Epoxy overmoulded	
	Color:	Black	
Electrical:	Operating frequency:	125 kHz ± 6 kHz	* At room temperature
	Min. flux density:	18µT RMS	* At RT for read mode at 125 kHz
Chemical:	Water immersion IP68		* 20°C, 24h, 2m
	HCL (10%), gasoline,		* 20°C, 100h
	Bleach, formic acid,		* 20°C, 100h
	Caustic soda, oil		* 20°C, 100h
Mechanical:	Isostatic pression:	300 bars	* 5min
	Axial compression strength:	1000N	* 10s
	Radial compression strength:	1000N	* 10s
	Vibration	IEC 68.2.6	* 10g, 10...2000 Hz, 3 axis, 2.5h
	Schock	IEC 68.2.27	* 40g, 18ms, 6 axis, 2000 times
Thermal:	Storage:	-25°C to +120 °C	* 1x 1000h
		+160 °C	* 1x 35h
		+220 °C	* 1x 30s
	Shock/fatigue:	+20°C to +160 °C	* 100x 5min with transposition in 20s
	Operating:	-25°C to +85°C	
Application:	Typical laundry process qualified: Washing 40min (12min. at 90°C) Water press extraction 20 bars 3min. Spin dryer 10min. 175°C Tunnel finisher 10min 175°C		
Part number:	601106		